






VITI A ESAGONO INTERNO






Tabella N. 4

Diametro viti corrispondente all'inserto esagonale

Misure metriche

 Ø Viti mm	 mm		
			
	Viti a testa cilindrica	Viti a testa fresata	Viti senza testa ISO 4026
1,6	1,5		0,7
2	1,5		0,9
2,5	2		1,3
3	2,5	2	1,5
4	3	2,5	2
5	4	3	2,5
6	5	4	3
8	6	5	4
10	8	6	5
12	10	8	6
14	12	10	
16	14	10	8
18	14		
20	17	12	10
22	17		
24	19		12
27	19		
30	22		
33	24		
36	27		
42	32		

Misure in pollici

 Ø Viti mm	 "						
							
	Viti a testa cilindrica	Viti a testa fresata	Viti senza testa ISO 4026	"	mm	"	mm
n° 0	1,52	0,50	1,27	,035	0,89	,028	0,711
n° 1	1,85	1/16	1,59	,050	1,27	,035	0,89
n° 2	2,18	5/64	1,98	,050	1,27	,035	0,89
n° 3	2,51	5/64	1,98	1/16	1,59	,050	1,27
n° 4	2,84	3/32	2,38	1/16	1,59	,050	1,27
n° 5	3,17	3/32	2,38	5/64	1,98	1/16	1,59
n° 6	3,5	7/64	2,78	5/64	1,98	1/16	1,59
n° 7	3,5	1/8	3,17				
n° 8	4,16	9/64	3,57	3/32	2,38	5/64	1,98
n° 10	4,82	5/32	3,97	7/64	2,78	3/32	2,38
n° 10	4,82			1/8	3,17		
1/4	6,35	3/16	4,75	9/64	3,57	7/64	2,78
1/4	6,35	7/32	5,55	5/32	3,97	1/8	3,17
5/16	7,94	1/4	6,35	3/16	4,75	9/64	3,57
5/16	7,94					5/32	3,97
3/8	9,52	5/16	7,94	7/32	5,55	3/16	4,75
7/16	11,11	3/8	9,52	1/4	6,35	7/32	5,55
1/2	12,7	3/8	9,52	5/16	7,94	1/4	6,35
5/8	15,87	1/2	12,7	3/8	9,52	5/16	7,94
3/4	19,05	5/8	15,88	1/2	12,7	3/8	9,52
7/8	22,2	3/4	19,05	9/16	14,29	1/2	12,7
1	25,4	3/4	19,05	5/8	15,88	9/16	14,29
1"1/8	28,57	7/8	22,2	3/4	19,05	9/16	14,29
1"1/4	31,75	7/8	22,2	7/8	22,2	5/8	15,88
1"3/8	34,92	1"	25,4	7/8	22,2	5/8	15,88
1"1/2	38,10	1"	25,4	1"	25,4	3/4	19,05