

Misure barrate ESAURITE

8738E

SCU



TiAIN



HSS-E-8%

Descrizione di riferimento vedi Art. 8738

In acciaio SUPER-RAPIDO HSS-E al COBALTO 8% con rivestimento TiAIN.

Ø.....	mm	4	5	6	8	10	12	14
Lungh. totale.....	mm	51	52	52	61	63	73	73
Lungh. tagliente.....	mm	7	8	8	11	13	16	16
Attacco Ø.....	mm	6	6	6	10	10	12	12
8738E	Cad.	57,60	57,60	57,60	67,70	67,70	82,60	105,00
Ø.....	mm	16	18	20				
Lungh. totale.....	mm	79	79	82				
Lungh. tagliente.....	mm	19	19	22				
Attacco Ø.....	mm	16	16	20				
8738E	Cad.	119,00	140,00	160,00				

Articolo in esaurimento.

8739

SCU



HSS-E-8%

Tipo a 2 taglianti elicoidali e punta semisferica. Serie lunga. ISO 1641/1.

Attacco DIN 6535 HB/1835-1B. Tolleranza tagli. e8.

In acciaio SUPER-RAPIDO HSS-E al COBALTO 8%.

Ø.....	mm	3	4	5	6	8	10	12
Lungh. totale.....	mm	56	63	68	68	88	95	110
Lungh. tagliente.....	mm	8	11	13	13	19	22	26
Attacco Ø.....	mm	6	6	6	6	10	10	12
8739	Cad.	48,50	48,50	48,50	46,10	59,70	64,20	80,60
Ø.....	mm	14	16	18	20			
Lungh. totale.....	mm	110	123	123	141			
Lungh. tagliente.....	mm	26	32	32	38			
Attacco Ø.....	mm	12	16	16	20			
8739	Cad.	101,00	117,00	139,00	164,00			

8742

SCU



HSS-E-8%

Tipo a 3 taglianti elicoidali. Serie corta. DIN 844 A - UNI 8244 A - ISO 1641/1.

Dente frontale al centro. Attacco DIN 6535 HB/1835-1B. Tolleranza tagli. e8

In acciaio SUPER-RAPIDO HSS-E al COBALTO 8%.

Ø.....	mm	3	4	5	6	7	8	9	10	11
Lungh. totale.....	mm	52	55	57	57	66	69	69	72	79
Lungh. tagliente.....	mm	8	11	13	13	16	19	19	22	22
Attacco Ø.....	mm	6	6	6	6	10	10	10	10	12
8742	Cad.	27,30	27,10	25,10	25,10	40,30	38,10	43,70	40,30	54,30
Ø.....	mm	12	13	14	15	16	18	20	22	
Lungh. totale.....	mm	83	83	83	92	92	104	104	104	
Lungh. tagliente.....	mm	26	26	26	32	32	32	38	38	
Attacco Ø.....	mm	12	12	12	16	16	16	20	20	
8742	Cad.	50,80	60,50	58,00	70,90	69,80	81,60	93,30	132,00	

8743

SCU



TiAIN

HSS-E-8%

Descrizione di riferimento vedi Art. 8742

In acciaio SUPER-RAPIDO HSS-E al COBALTO 8% con rivestimento TiAIN.

Ø.....	mm	4	5	6	8	10	12	14
Lungh. totale.....	mm	55	57	57	69	72	83	83
Lungh. tagliente.....	mm	11	13	13	19	22	26	26
Attacco Ø.....	mm	6	6	6	10	10	12	12
8743	Cad.	39,20	38,20	38,20	59,10	60,40	74,10	83,10
Ø.....	mm	16	18	20				
Lungh. totale.....	mm	92	92	104				
Lungh. tagliente.....	mm	32	32	38				
Attacco Ø.....	mm	16	16	20				
8743	Cad.	108,00	122,00	133,00				

8746

SCU



HSS-E-8%

Tipo a 3 taglianti elicoidali. Serie lunga. UNI 8245 A - ISO 1641/1.

Dente frontale al centro. Attacco DIN 6535 HB/1835-1B. Tolleranza tagli. e8.

In acciaio SUPER-RAPIDO HSS-E al COBALTO 8%.

Ø.....	mm	3	4	5	6	8	10	12
Lungh. totale.....	mm	56	63	68	68	88	95	110
Lungh. tagliente.....	mm	12	19	24	24	38	45	53
Attacco Ø.....	mm	6	6	6	6	10	10	12
8746	Cad.	36,90	34,60	33,30	35,60	52,70	50,40	63,80
Ø.....	mm	14	16	18	20			
Lungh. totale.....	mm	110	123	123	141			
Lungh. tagliente.....	mm	53	63	63	75			
Attacco Ø.....	mm	12	16	16	20			
8746	Cad.	71,10	89,10	104,00	121,00			