

Misure barrate **ESAURITE**

FRESE CILINDRICHE FRONTALI (end mills)

8751

SCU



HSS-E-8%

Prod. SCU

Tipo a taglienti elicoidali. Serie corta. DIN 844 A - UNI 8244 - ISO 1641/1.
Attacco DIN 6535 HB/1835-1B. Tolleranza tagl. J14.
Ø mm 3 a 22 = 4 tagl./Ø mm 25 e 28 = 5 tagl./Ø mm 30 = 6 tagl.
In acciaio SUPER-RAPIDO HSS-E al COBALTO 8%.

Ø.....	mm	3	4	5	6	7	8	9	10
Lungh. totale.....	mm	52	55	57	57	66	69	69	72
Lungh. tagliente.....	mm	8	11	13	13	16	19	19	22
Attacco Ø.....	mm	6	6	6	6	10	10	10	10
8751	Cad.	24,50	23,20	22,70	22,70	36,70	34,30	39,10	36,70
Ø.....	mm	11	12	13	14	15	16	17	18
Lungh. totale.....	mm	79	83	83	83	92	92	92	92
Lungh. tagliente.....	mm	22	26	26	26	32	32	32	32
Attacco Ø.....	mm	12	12	12	12	16	16	16	16
8751	Cad.	50,70	48,30	55,30	51,80	63,80	61,60	78,60	73,60
Ø.....	mm	19	20	22	25	28	30		
Lungh. totale.....	mm	92	104	104	121	121	121		
Lungh. tagliente.....	mm	32	38	38	45	45	45		
Attacco Ø.....	mm	20	20	20	25	25	25		
8751	Cad.	90,70	84,50	119,00	179,00	202,00	244,00		

8751E

SCU



TiAIN

HSS-E-8%

Descrizione di riferimento vedi Art. 8751

In acciaio SUPER-RAPIDO HSS-E al COBALTO 8% con rivestimento TiAIN.

Ø.....	mm	4	5	6	8	10	12	14
Lungh. totale.....	mm	55	57	57	69	72	83	83
Lungh. tagliente.....	mm	11	13	13	19	22	26	26
Attacco Ø.....	mm	6	6	6	10	10	12	12
8751E	Cad.	35,40	35,20	35,20	53,80	56,20	70,90	74,40
Ø.....	mm	16	18	20				
Lungh. totale.....	mm	92	92	104				
Lungh. tagliente.....	mm	32	32	38				
Attacco Ø.....	mm	16	16	20				
8751E	Cad.	98,50	111,00	124,00				

8753

SCU



HSS-E-8%

Tipo a 4 taglienti elicoidali. Serie lunga. UNI 8245 A - ISO 1641/1.

Attacco DIN 6535 HB/1835-1B. Tolleranza tagl. J14.

In acciaio SUPER-RAPIDO HSS-E al COBALTO 8%.

Ø.....	mm	3	4	5	6	7	8	9
Lungh. totale.....	mm	56	63	68	68	80	88	95
Lungh. tagliente.....	mm	12	19	24	24	30	38	45
Attacco Ø.....	mm	6	6	6	6	10	10	10
8753	Cad.	34,30	33,20	31,90	30,80	53,10	50,70	53,10
Ø.....	mm	10	11	12	13	14	15	16
Lungh. totale.....	mm	95	102	110	110	110	123	123
Lungh. tagliente.....	mm	45	45	53	53	53	63	63
Attacco Ø.....	mm	10	12	12	12	12	16	16
8753	Cad.	48,20	68,10	61,90	75,60	69,40	87,90	82,90
Ø.....	mm	17	18	19	20	22		
Lungh. totale.....	mm	123	123	123	141	141		
Lungh. tagliente.....	mm	63	63	63	75	75		
Attacco Ø.....	mm	16	16	20	20	20		
8753	Cad.	108,00	99,50	168,00	121,00	164,00		

Misura mm 19 in esaurimento.

8755

SCU



HSS-E-5%

Tipo a taglienti elicoidali. Serie corta. DIN 845 B - UNI 8250 - ISO 1641/2.

Attacco Cono Morse e foro filettato. Tolleranza tagl. J14.

Ø mm 14 a 22 = 4 tagl./Ø mm 24 e 25 = 5 tagl./Ø mm 30 e 32 = 6 tagl.

In acciaio SUPER-RAPIDO HSS-E al COBALTO 5%.

Ø.....	mm	14	15	18	20	22	24
Lungh. totale.....	mm	117	117	117	123	140	147
Lungh. tagliente.....	mm	32	32	32	32	33	45
Attacco.....	C.M.	2	2	2	2	3	3
8755	Cad.	127,00	127,00	135,00	142,00	177,00	189,00
Ø.....	mm	25	30				
Lungh. totale.....	mm	147	147				
Lungh. tagliente.....	mm	45	45				
Attacco.....	C.M.	3	3				
8755	Cad.	194,00	261,00				

Articolo in esaurimento.

Tutte le immagini sono inserite a scopo illustrativo. I prodotti possono subire modifiche.

Prezzi in EURO - IVA esclusa