

Misure barrate ESAURITE

8770

SCU

HSS-E-5%



Tipo per SGROSSARE a taglienti elicoidali. Serie corta. DIN 845 B - UNI 8250 - ISO 1641/2. Attacco Cono Morse e foro filettato. Tolleranza tagl. J14. Ø mm 16 a 22 = 4 tagl./Ø mm 24 a 32 = 5 tagl.

In acciaio SUPER-RAPIDO HSS-E al COBALTO 5%.

Ø.....	mm	16	18	20	22	24	28
Lungh. totale.....	mm	117	117	123	140	147	147
Lungh. tagliente.....	mm	32	32	38	38	45	45
Attacco	C.M.	2	2	2	3	3	3
	8770	Cad.	164,00	179,00	194,00	226,00	249,00

Articolo in esaurimento.

8771

SCU

HSS-E-8%



Descrizione di riferimento vedi Art. 8770

In acciaio SUPER-RAPIDO HSS-E al COBALTO 8%.

Ø.....	mm	16	18	20	22	24	26	28	30	32
Lungh. totale.....	mm	117	117	123	140	147	147	147	147	178
Lungh. tagliente.....	mm	32	32	38	38	45	45	45	45	53
Attacco	C.M.	2	2	2	3	3	3	3	3	4
	8771	Cad.	138,00	138,00	185,00	199,00	220,00	245,00	262,00	291,00

8775

SCU

HSS-E-8%



Tipo a passo fine per SGROSSARE a 4 taglienti elicoidali. Serie corta.

DIN 844 A - UNI 8244A - ISO 1641/1. In acciaio SUPER-RAPIDO HSS-E al COBALTO 8%.

Attacco DIN 6535 HB/1835-1B. Tolleranza tagl. J14. Per ottenere una superficie più fine.

Ø.....	mm	10	12	14	16	18	20	22	
Lungh. totale.....	mm	72	83	83	92	92	104	104	
Lungh. tagliente.....	mm	22	26	26	32	32	38	38	
Attacco Ø.....	mm	10	12	12	16	16	20	20	
	8775	Cad.	75,20	84,20	89,80	103,00	116,00	143,00	156,00

8779

SCU

HSS-E-5%



Tipo a denti elicoidali rinforzati. Esecuzione N. DIN 1880 - UNI 3903 - ISO 2586.

In acciaio SUPER-RAPIDO HSS-E al COBALTO 5%.

Chiavetta trasversale. Tolleranza tagl. J16.

Ø.....	mm	40	50	63	80	
Spessore	mm	32	36	40	45	
Ø foro	mm	16	22	27	27	
Denti.....	Nr	8	8	8	10	
	8779	Cad.	168,00	219,00	314,00	468,00

8781

SCU

HSS-E-5%



Tipo a denti elicoidali rinforzati. Esecuzione N. DIN 841.

In acciaio SUPER-RAPIDO HSS-E al COBALTO 5%.

Chiavetta longitudinale. Tolleranza tagl. J16.

Ø.....	mm	30	35	40	50	60	75	
Spessore	mm	30	35	40	50	60	75	
Ø foro	mm	13	16	16	22	27	27	
Denti.....	Nr	8	8	8	8	8	10	
	8781	Cad.	158,00	172,00	202,00	299,00	414,00	674,00

8782F

SCU

HSS-E-5%



Tipo per SEMIFINIRE a denti elicoidali. DIN 1880 - UNI 3903 - ISO 2586.

In acciaio SUPER-RAPIDO HSS-E al COBALTO 5%.

Chiavetta trasversale. Tolleranza tagl. J16.

Ø.....	mm	40	50	63	80	
Spessore	mm	32	36	40	45	
Ø foro	mm	16	22	27	27	
Denti.....	Nr	6	8	8	8	
	8782F	Cad.	222,00	289,00	407,00	656,00