

1813T**SCU**

Tipo a disco, a fascia stretta, con possibilità di uso anche accoppiato, con fili d'acciaio HSS ondulati ad alta resistenza e foro centrale. Ø fili mm 0,30.

Ø e spessore	mm	100x13	125x13	150x16	180x18	200x20	250x30
Ø foro	mm	16	16	16	20	20	25
1813T	Cad.	16,50	17,40	30,80	34,60	33,10	55,50

1814A**SCU**

Tipo a disco con fili d'acciaio ottonato, ondulati e foro centrale. Ø fili mm 0,30.

Ø e spessore	mm	120x20	150x20	200x20	200x28
Ø foro	mm	16	16	20	20
1814A	Cad.	13,10	17,10	20,10	26,10

1814G**SCU**

Tipo a disco con fili d'acciaio HSS ondulati ad alta resistenza e foro centrale. Ø fili mm 0,30.

Ø e spessore	mm	80x18	100x17	100x24	125x25	150x25	150x30	200x30
Ø foro	mm	13	16	16	16	16	16	20
1814G	Cad.	14,80	15,20	21,60	21,90	28,10	38,10	49,40
Ø e spessore	mm	200x50	250x30	250x60	300x45	300x60		
Ø foro	mm	20	25	25	30	30		
1814G	Cad.	77,10	87,70	153,00	125,00	171,00		

HSS**1816G****SCU**

Tipo in filo d'acciaio INOX, a disco con foro centrale.

Ø e spessore	mm	150x25	150x30	200x30	200x40	250x30	250x40
Ø foro	mm	16	16	20	20	25	25
1816G	Cad.	43,30	57,70	67,40	102,00	140,00	193,00

INOX**1816T****SCU**

Tipo in filo di ottone, a disco con foro centrale. Ø fili mm 0,30.

Ø e spessore	mm	150x25	200x30	250x30
Ø foro	mm	16	20	25
1816T	Cad.	78,10	88,50	283,00

OTTONE